

LOVERE

A L U M I N I U M R A D I A T O R S



® **GLOBAL** 
R A D I A T O R I

LOVERE



HIGH THERMAL OUTPUT Guaranteed by certification, according to the norm EN 442, from the *Politecnico* in Milan. The high thermal output allows less bulky radiators to be installed.

ENERGY SAVING WITH MAXIMUM COMFORT With the Global radiators the regulation of the temperature is easy and inexpensive. An ideal temperature for every environment according to personal needs is rapidly achieved.

VERY LONG DURATION Thanks to the high quality of the material, that gives the maximum guarantee of resistance and duration. The double protection in the "anaphoresis-bath" followed with epoxy power enameling guarantees a perfect and durable finish.

EASIER INSTALLATION Due to the lightness of the aluminum and the sectional elements that allow greater ease and flexibility of installation.

CERTIFIED QUALITY AND ENVIRONMENTAL The ICIM certified on 1994 (norm ISO 9001:2000) the Quality System and on 2001 (norm UNI EN ISO 14001) the System of Environmental Management.

GLOBAL provides a 10 year warranty from the production date

(stamped on the side of each sections)
The conventional warranty grants the sole right to free replacement of the radiator which, due to defects originating from defects in material or workmanship, is not fit for purpose or its ordinary intended use. Replacement radiators shall be delivered free of charge to the retailer who sold the radiator to the end customer or his installer.

The warranty is valid on the condition that the installation and the system to which the product is connected are performed by qualified/authorised personnel to top workmanship standards and in compliance with the regulations and requirements of the sector in force; it is also valid on the condition that there has been full compliance with warnings and instructions for proper installation, use and maintenance of the product indicated in the technical documentation under the paragraph entitled *correct installation, use and maintenance instructions*, available and downloadable from the **TECHNICAL INFO** section on the globalradiatori.it website. The warranty is regulated by further conditions indicated in the technical catalogue and the CONVENTIONAL WARRANTY section on the globalradiatori.it website.

LOVERE	dimensions mm				Ø connection	dry weight approx. Kg	water content litres	heat output EN 442		exponent n	coefficient Km
	A	B	C	D				ΔT 50°C	ΔT 30°C		
	overall height	width	depth	pipe centres				Watt	Watt		
800	875	80	95	800	1"	1,80	0,61	160	81	1,32708	0,88901
700	775	80	95	700	1"	1,60	0,55	143	73	1,31451	0,83571
600	675	80	95	600	1"	1,40	0,51	127	65	1,30194	0,77624
500	575	80	95	500	1"	1,20	0,46	110	57	1,28800	0,71350
350	425	80	95	350	1"	0,93	0,37	82	43	1,26969	0,57402

* 1 Watt = 0,863 Kcal/h

The heat output is certified by the Institute of Engineering *Politecnico* in Milan according to the norm EN 442.



EXAMPLE FOR A DIFFERENT ΔT

If you need to know a radiator heat output (P) with different ΔT from Δt 50°C, use the following characteristic equation: $P = Km \cdot \Delta T^n$

Example for the 600 model with ΔT = 60°C → $P = 0,77624 \cdot 60^{1,30194} = 161$ Watt

HEAT OUTPUT READINGS WITH DIFFERENT ΔT

LOVERE	ΔT 20°C	ΔT 25°C	ΔT 30°C	ΔT 35°C	ΔT 40°C	ΔT 45°C	ΔT 50°C	ΔT 55°C	ΔT 60°C
800	47	64	81	99	119	139	160	181	203
700	43	57	73	89	107	125	143	162	182
600	39	52	65	80	95	111	127	144	161
500	34	45	57	69	82	96	110	124	139
350	26	34	43	52	62	72	82	93	104


The expected heat output is obtained by observing the distances specified below:

≥ cm 2 from the wall

≥ cm 10 from the floor

≥ cm 10 from the shelf or window-sills

In order to prevent the thermal expansion of the system from causing noise in correspondence with the heaters, it is advisable to use plastic brackets to support the radiators (items A004, A025, A027 or A029 in our catalogue).



CORRECT INSTALLATION, USE AND MAINTENANCE INSTRUCTIONS

- ★ Lovere radiators can be used in all hot water or vapour heating installations up to 110°C with a working pressure up to 1600 K Pascal - 16 bar.
- ★ They can be installed in systems with iron, copper or thermoplastic pipes.
- ★ In order to protect the system from scaling and corrosion processes, which affect radiators, pipes and boilers, the UNI-CTI 8065 Standard provides for the treatment of the filling water of the system, without distinguishing between aluminium, steel or cast iron.
- ★ Among the various products to be added to the system in accordance with the abovementioned UNI Standard, there is a specific one for aluminium, an aliphatic film-forming polyamine marked under the name Cillit-HS 23 Combi in the quantity recommended by the manufacturer. However, it is useful to check the pH value of the water, which should preferably be between 6.5 and 8.
- ★ It is recommended to install automatic air vent valves on each radiator.
- ★ Avoid closing the radiator shut-off valves completely in order to allow any gas that may be inside the radiators to escape through the automatic air vent valve that is compulsory in every heating system, thus avoiding possible overpressure that could damage the radiators.
- ★ If one or more batteries are to be excluded from the circuit, an automatic air vent must be fitted to each battery.
- ★ For a good preservation of the paint, it is necessary that the radiators, before and after installation, are not kept in very humid environments (inside showers, in saunas, in Turkish baths, near swimming pools, etc.). If paint comes off at one point on the radiator, aluminium oxide can form and cause the paint to peel off completely. Do not use porous clay humidifiers.
- ★ To clean the outside and surfaces near the radiator, it is necessary to avoid the use of abrasive or chemically corrosive/aggressive products of any nature: we recommend water and neutral cleaning. The operation must be carried out when the radiator is cold to preserve the original brilliance of the paint over time.
- ★ Do not place weights and/or objects on the radiators. Do not use radiators for any purpose other than as a heater (e.g.: as a bench/stand, ladder, to store furniture or objects).



ACCESSORIES



A001 galvanized straight bracket



ANGLE BRACKET

A003 galvanized
A004 white plastic



EXPANSION PLUG BRACKETS


A025 170 mm white or special colours (pair)
A026 195 mm white or special colours (pair)



A027 universal brackets white blister pack (pair)



A029 square brackets white blister pack (pair)



WHITE WALL BRACKET

A033 800 mm
A034 700 mm
A035 600 mm
A036 500 mm
A037 350 mm



A015 white floor fixing system



A237 white handy grip
A238 chrome handy grip



TOWEL RAILS

A201 48 cm white
A202 48 cm chrome
A207 32 cm white
A208 32 cm chrome



A010 RAL 9010 white or special colours spray can



A017 RAL 9010 white marker



REDUCER KIT WITH SILICONE GASKETS AND ADJUSTABLE VALVE

A043 3/8" for 200/D radiators - 800 mm - white or chrome
A046 1/2" for 200/D radiators - 800 mm - white, chrome, special colours
A048 3/4" for 200/D radiators - 800 mm - white or chrome



REDUCER KIT WITH SILICONE GASKETS AND VALVE WHITE HANDWHEEL

A190 3/8" for 200/D radiators - 800 mm - white
A192 1/2" for 200/D radiators - 800 mm - white



A009 1" nipple



A018 Cillit HS 23 Combi liquid



A079 hex key with lever
A080 hex key 500 mm
A081 hex key 800 mm



1" BLIND PLUG OR REDUCER

A005 white
A006 galvanized
A020 white with silicone gasket



GASKETS

A007 1" plug 1,50 mm
A008 1" nipple 1,00 mm
A021 silicone - for plugs and reducers



A013 1" float type air vent valve right or left



MANUAL AIR VENT VALVE

A012 1/8" **A040** 3/8"
A039 1/4" **A050** 1/2"



A041 1/2" adjustable manual air vent valve - white



A042 1/2" automatic air vent valve - chrome



A038 1/2" adjustable manual air vent valve - chrome



A019 plug wrench



cod. 10
white glossy
RAL 9010



cod. 11
white sand
RAL 9016



cod. 12
white matt



cod. 01
ivory glossy
RAL 1013



cod. 05
metallic matt beige



cod. 06
metallic matt quartz



cod. 07
metallic matt dark grey



cod. 08
metallic matt silver grey



cod. 09
metallic matt rust



cod. 14
black matt

standard colour **special colours** see the Colour Card

The colours are indicative. For technical printing reasons, it is no possible to faithfully reproduce the paints used. The colour of the products supplied may differ from that shown in this catalogue.



GLOBAL di Fardelli Ottorino & C. s.r.l.

24060 ROGNO (BG) ITALIA • via Rondinera, 51
tel. ++39 035977111 • fax ++39 035977110
globalradiatori.it • info@globalradiatori.it

